

Product information

Product description:	SOLL PLASTIC - is a one-component primer for plastic parts, which can be applied by brush or spray gun. Used in car refinishing as a primary layer, which provides an appropriate micro-layer and improves the adhesion to the plastic top layer.
Usage:	Ready to use for application by brush or spray gun in an amount of 1-2 layers in the intervals between the layers of about 10 minutes. Drying time 20-30 minutes at 20 °C temperature. After this time each layer can be applied topcoat.
Form:	Liquid
Colour:	Colourless
Packing:	1 l
Storage and shelf life:	Store in the original, unopened package in a cool, dry place, away from sources of ignition and heat. Avoid sunlight. Shelf life: 12 months, at 20 °C temperature.
Notes:	<p>The above information and our technical indications (both verbal and written or resulting from test), in particular those that regard the applications and uses of our products, correspond to our best knowledge and experience; however, they do not constitute our warranty relative to final results or our responsibility deriving from any juridical relationship whatsoever.</p> <p>In fact, considering the multiplicity of materials, supports, handling and storage conditions, as well as the conditions of production and utilization, the user, in function of his specific circumstances of use, must always preventively verify all the information and instructions reported above.</p> <p>No assertion contained in this publication is to be considered authorization or suggestion to violate any industrial property rights of third parties.</p>